

HEAVY-DUTYCASTER.COM



PHIL@HEAVY-DUTYCASTER.COM


336-362-1639

https://www.heavy-dutycaster.com/

Medium Duty Stainless Steel Casters With Solid Polyurethane wheel with SS Precision Ball Bearings

Part #	Swivel/Rigid	Wheel Size (Diameter x Tread Width), Wheel Material, Bearings, Color	Capacity	Overall Height	Price Each	Shipping Locations
S6640-01-SPU	Swivel	4" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	800#	5-5/8 in.	\$89.00	GA, IL
S6640-01-SPU-TLB	Swivel w/ Top Lock Brake	4" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	800#	5-5/8 in.	\$95.00	GA, IL
S6640R-01-SPU	Rigid	4" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	800#	5-5/8 in.	\$82.00	GA, IL
S6640-01-HU	Swivel	4" x 2" Ergolastimer w/ Stainless Steel Ball Bearings; Grey	800#	5-5/8 in.	\$105.00	GA, IL
S6640-01-HU-TLB	Swivel w/ Top Lock Brake	4" x 2" Ergolastomer w/ Stainless Steel Ball Bearings; Grey	800#	5-5/8 in.	\$112.00	GA, IL
S6640R-01-HU	Rigid	4" x 2" Ergolastomer w/ Stainless Steel Ball Bearings; Grey	800#	5-5/8 in.	\$104.00	GA, IL





Part #	Swivel/Rigid	Wheel Size (Diameter x Tread Width), Wheel Material, Bearings, Color	Capacity	Overall Height	Price Each	Shipping Locations
S6650-01-SPU	Swivel	5" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	900#	6.5 in.	\$112.00	GA, IL
S6650-01-SPU-TLB	Swivel w/ Top Lock Brake	5" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	900#	6.5 in.	\$128.00	GA, IL
S6650R-01-SPU	Rigid	5" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	900#	6.5 in.	\$110.00	GA, IL
S6650-01-HU	Swivel	5" x 2" Ergolastimer w/ Stainless Steel Ball Bearings; Grey	1,000#	6.5 in.	\$135.00	GA, IL
S6650-01-HU-TLB	Swivel w/ Top Lock Brake	5" x 2" Ergolastomer w/ Stainless Steel Ball Bearings; Grey	1,000#	6.5 in.	\$150.00	GA, IL
S6650R-01-HU	Rigid	5" x 2" Ergolastomer w/ Stainless Steel Ball Bearings; Grey	1,000#	6.5 in.	\$102.00	GA, IL



5" x 2" Stainless steel swivel caster with top lock brake

Part #	Swivel/Rigid	Wheel Size (Diameter x Tread Width), Wheel Material, Bearings, Color	Capacity	Overall Height	Price Each	Shipping Locations
S6660-01-SPU	Swivel	6" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	900#	6.5 in.	\$146.00	GA, IL
S6660-01-SPU-TLB	Swivel w/ Top Lock Brake	6" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	900#	6.5 in.	\$156.00	GA, IL




S6660R-01-SPU	Rigid	6" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	900#	6.5 in.	\$145.00	GA, IL
S6660-01-HU	Swivel	6" x 2" Ergolastimer w/ Stainless Steel Ball Bearings; Grey	1,000#	6.5 in.	\$168.00	GA, IL
S6660-01-HU-TLB	Swivel w/ Top Lock Brake	6" x 2" Ergolastomer w/ Stainless Steel Ball Bearings; Grey	1,000#	6.5 in.	\$178.00	GA, IL
S6660R-01-HU	Rigid	6" x 2" Ergolastomer w/ Stainless Steel Ball Bearings; Grey	1,000#	6.5 in.	\$165.00	GA, IL



	Part #	Swivel/Rigid	Wheel Size (Diameter x Tread Width), Wheel Material, Bearings, Color	Capacity	Overall Height	Price Each	Shipping Locations
	S6680-01-SPU	Swivel	8" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	900#	6.5 in.	\$166.00	GA, IL
S	\$6680-01-SPU-TLB	Swivel w/ Top Lock Brake	8" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	900#	6.5 in.	\$176.00	GA, IL
	S6680R-01-SPU	Rigid	8" x 2" Solid Polyurethene w/ Stainless Steel Roller Bearings or Delrin Bearings; Blue	900#	6.5 in.	\$162.00	GA, IL
	S6680-01-HU	Swivel	8" x 2" Ergolastimer w/ Stainless Steel Ball Bearings; Grey	1,000#	6.5 in.	\$202.00	GA, IL
	S6680-01-HU-TLB	Swivel w/ Top Lock Brake	8" x 2" Ergolastomer w/ Stainless Steel Ball Bearings; Grey	1,000#	6.5 in.	\$212.00	GA, IL
	S6680R-01-HU	Rigid	8" x 2" Ergolastomer w/ Stainless Steel Ball Bearings; Grey	1,000#	6.5 in.	\$200.00	GA, IL
















- Polished 304 STAINLESS STEEL provides an attractive appearance
- Highly resistant to conditions that would normally corrode and rust regular steel easters.
- Seals in both the upper and lower raceways standard. Seals must be removed for high-temp applications over 160 degrees Fahrenheit
- Double ball raceways provide extra capacity & durability
- 5/8" nut and bolt kingpin
- Applications: Ideal for wet, damp conditions or other corrosive environments such as wash downs, restaurants, food processing plants, hospitals & other institutional applications, etc



Raceway seals are standard on our stainless steel swivel casters.